

Applications

- Alarm panel Battery backup
- CCTV Battery backup
- Backup power supply for door controller
- Maglock for an Access Control solution

Features

- Microprocessor Controlled charging output
- Low battery switch off at 10V DC
- Buzzer tones on battery low and AC Fail
- Resettable Fuse protection on output
- Fuse protection on AC input
- ABS Plastic enclosure

Certifications

- EN 55022:2010; EN 55024:2010
- EN 6100-3-2:2006+A1:2009 + A2:2009
- EN 6100-3-3:2008; IEC 60950-1:2005 + A1:2009

Description

6.4 AMP Power-Supply

Battery charger with Low Battery Cut Out



Specifications

- Input Voltage Range: 110V ~ 230V AC 50Hz
- Output Voltage: 13V ~ 14.4V Adjustable
- Max Current output: 6.4A DC / 70Watts
- Relay contact rating: 10A
- AC Fail output rating: 140mA Positive switching
- Operating temp: -3°C to 60°C
- Dimensions (lxbxh): 275 x 225 x 97mm
- Gross Weight: 1.13kg
- Warranty: 12 Months

Applications

- Alarm panel Battery backup
- CCTV Battery backup
- Backup power supply for door controller
- Maglock for an Access Control solution

Features

- Microprocessor Controlled charging output
- Low battery switch off at 10V DC
- Buzzer tones on battery low and AC Fail
- Resettable Fuse protection on output
- Fuse protection on AC input
- ABS Plastic enclosure

Certifications

- EN 55022:2010; EN 55024:2010
- EN 6100-3-2:2006+A1:2009 + A2:2009
- EN 6100-3-3:2008; IEC 60950-1:2005 + A1:2009

Description

3.2 AMP Power-Supply
Battery charger with Low Battery Cut Out



Specifications

- Input Voltage Range: 110V ~ 230V AC 50Hz
- Output Voltage: 13V ~ 14.4V Adjustable
- Max Current output: 3.2A DC / 40Watts
- Relay contact rating: 10A
- AC Fail output rating: 140mA Positive switching
- Operating temp: -3°C to 60°C
- Dimensions (lxbxh): 200 x 180 x 87mm
- Gross Weight: 0.895Kg
- Warranty: 12 Months